

PondSeal

	compacted or pure layer water cont	ainment membranes.
APPLICATION	• Soil Sealant	• Tailings Ponds
	Reservoirs	• Leach Pads
	Municipal Landfills	• Canals
	Sanitation Lagoons	• Tank Farms
	Hazardous Storage	• Ponds
	This analysis is	typical, variations can apply
TYPICAL	Product Specification	Typical PondSeal
PROPERTIES	Color	Tan/Red
	Density	95 lbs/ft ³ (compact)
	рН	8.5 to 9.0
	Swell	19 сс
	Moisture	8 to 12 wt.%
	This analysis is ty	pical, variations can apply
SIEVE	SCREEN MESH %	
ANALYSIS	+4	19
	+12	37
	+20	49
	+200	95
ADVANTAGES	• 100% Natural	Great containment barrier
	 Ultra low permeability barrier 	 Mixes quickly and easily
	Wide range of use	Excellent hard water performance
MIXING	The percent of PondSeal used should be determined through permeability testing and user specification requirements.	
	Permeability testing is available at Redmond Minerals upon request.	
PACKAGING	PondSeal is available in 50 lb plastic bags (60 bags per pallet), and is also available in 3,000 lb. super sacks and bulk shipments.	
VAILABILITY	To order PondSeal please contact us at: 1-866-440-2529	

To the best of our knowledge and belief, the above information is accurate. Because the conditions of handling and use are beyond our control, we cannot guarantee results, and assume no liability for damages incurred in using our product. 7/15